Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-047-0682

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.179 inches

Body Diameter:

0.500 inches

Shaft Diameter:

0.187 inches

Shaft Length:

1.062 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.125 inches

Overall Diameter:

0.670 inches

Undercut Diameter:

0.1248 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

335.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

1.50 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.200 inches

Shaft End Play:

0.00800 inches

Pilot Diameter Runout:

0.00600 inches

Shaft Radial Play:

0.004 inches



Undercut Length:
0.500 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.000 kilohms all sections
Rotary Actuator Travel In Angular Deg:
345.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 all sections
Power Dissipation Rating Per Section In Watts:
0.25 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Special Features:
Inner shaft flat height 0.107 in., inner shaft flat length 0.218 in.
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-01-047-0682

Nonprecision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

