Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-047-1538

y:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

#### **Body Diameter:**

0.820 inches

#### **Body Length:**

0.500 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### **Fragility Factor:**

Moderately delicate

### Terminal Location:

Radially positioned over less than half the circumference

### Mounting Method:

Terminal

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

#### Rotary Actuator Travel In Angular Deg:

240.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

## Power Dissipation Rating Per Section In Watts:

1.25 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Actuator Travel Control Feature:

Stops

## Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

# Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

## Shelf Life:

N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0