## NSN 5905-01-047-1544

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-047-1544

Section Quantity:
1
Body Style:
Rectangular
Terminal Length:
0.300 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.080 inches
Body Length:
0.375 inches
Body Width:
0.170 inches
Body Height:
0.420 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 5400.0 and 10800.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Features Provided:
Humidity proof
Electrical Resistance Per Section:
2.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 5400.0 and 10800.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 single section

0.5 free air single section

**Power Dissipation Rating Per Section In Watts:** 

## NSN 5905-01-047-1544

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Test Data Document:** 

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 pin

## **Specification Data:**

81349-mil-r-39035/2 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0