Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-047-1548

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# **Reliability Indicator:**

Not established

# Mounting Slot Width:

0.093 inches

#### Shaft Diameter:

0.080 inches

- Shaft Length:
- 0.035 inches

Body Length:

#### 0.500 inches

Body Width:

#### 0.187 inches

**Body Height:** 

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

7920.0

## Lateral Distance Between Mounting Hole Centers:

0.520 inches

#### **Mounting Facility Quantity:**

2

Terminal Location:

Rear end

#### **Mounting Method:**

Slot

#### Features Provided:

Humidity proof

#### **Electrical Resistance Per Section:**

100.0 ohms c and better flooring

#### **Rotary Actuator Travel In Angular Deg:**

7920.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# NSN 5905-01-047-1548

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

1.0 7th secondary quality

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Clutch

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

#### Fiig:

A002a0