NSN 5905-01-047-6213

Section Quantity:

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-047-6213

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.313 inches
Body Length:
1.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.70 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Maximum Stop Torque:
48.00 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
1.0
Fragility Factor:
Moderately rugged

NSN 5905-01-047-6213

Demilitarization:

Precision Wire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter:	
0.250 inches	
Screw Thread Series Designator:	
Jnef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Standard bushing	
Electrical Resistance Per Section:	
5.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
3600.0	
Function Conformity Tolerance Per Section:	
0.25/+0.25 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
150.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
30.0/+30.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
3.0/+3.0 single section	
Actuator Travel Control Feature:	
Stops	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
35.0 single section	
Test Data Document:	
31349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
3 turret	
Specification Data:	
31349-mil-r-12934/31 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5905-01-047-6213

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0