NSN 5905-01-047-6222

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-047-6222

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.200 inches
Shaft Diameter:
0.100 inches
Shaft Length:
0.040 inches
Body Length:
0.750 inches
Body Width:
0.190 inches
Body Height:
0.270 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
5400.0
Center To Center Distance Between Terminals:
0.500 inches
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
5400.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

NSN 5905-01-047-6222

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature C	Coefficient Of	Resistance	Per Section	on In Ppm	Per Deg (Celsius:
-100.0/+100.0 s	single section					

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0