

View Online at <https://aerobasegroup.com/nsn/5905-01-047-6912>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.75000 inches

Pilot Length:

0.06200 inches

Undercut Diameter:

0.750 inches

Undercut Width:

0.05200 inches

Body Diameter:

0.980 inches

Body Length:

0.682 inches

Mounting Lip Diameter:

0.88000 inches

Mounting Lip Depth:

0.06200 inches

Effective Electrical Rotation In Deg Angular Rotation:

342.0

Maximum Starting Torque:

0.30 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

20.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Function Characteristic Per Section:

Single section linear

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0