

View Online at <https://aerobasegroup.com/nsn/5905-01-047-7792>

Section Quantity:

1

Body Style:

Rectangular w/pointer adjustment

Reliability Indicator:

Not established

Terminal Length:

0.187 inches

Body Length:

0.250 inches

Body Width:

0.312 inches

Body Height:

0.375 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

280.0

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately delicate

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

2.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

280.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0