## NSN 5905-01-048-0510

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-048-0510 **Section Quantity: Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Actuator Type:** Integral knob with counter **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.498 inches **Terminal Location:** Rear end **Mounting Method:** Snap-in cup **Electrical Resistance Per Section:** 1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5905-01-048-0510

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0