Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-048-2577

Section	Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

#### **Terminal Length:**

0.300 inches

**Body Diameter:** 

0.500 inches

**Body Length:** 

0.235 inches

Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

315.0

### **Center To Center Distance Between Terminals:**

0.200 inches

**Terminal Location:** 

Rear end

### Mounting Method:

Terminal

### **Electrical Resistance Per Section:**

1.0 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

315.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

### Standard Taper Curve Per Section:

A single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0