NSN 5905-01-048-5357

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-048-5357 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.805 inches **Terminal Length:** 0.625 inches **Body Diameter:** 0.250 inches **Body Length:** 0.180 inches **Overall Diameter:** 0.250 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** Delicate **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Cubic Measure:** 0.011 cubic inches **Electrical Resistance Per Section:** 250.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 240.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

NSN 5905-01-048-5357

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.5 7th secondary quality
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0