NSN 5905-01-048-7890

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-048-7890 **Section Quantity: Shaft Diameter:** 0.250 inches **Shaft Length:** 0.250 inches Switch Type: Rotary **Effective Electrical Rotation In Deg Angular Rotation:** 285.0 **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 500.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 285.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Shelf Life: N/a

-

Unit Of Measure:

NSN 5905-01-048-7890

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	atio	

No

Fiig:

A002a0