Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-048-7890

S	Section Quantity:
1	
S	Shaft Diameter:
0	.250 inches
S	Shaft Length:
0	.250 inches
S	Switch Type:
R	Rotary
E	ffective Electrical Rotation In Deg Angular Rotation:
2	85.0
N	laximum Running Torque:
6	0.00 inch-ounces
N	laximum Stop Torque:
6	4.00 inch-ounces
N	Ionturn Device Location:
A	at 9 oclock
S	Screw Thread Diameter:
0	.375 inches
S	Screw Thread Series Designator:
ι	Inef
S	crew Thready Qty Per Inch (tpi):
3	2.0
N	Nounting Method:
S	Standard bushing
F	eatures Provided:
S	Switch
E	Electrical Resistance Per Section:
5	00.000 ohms single section
R	Rotary Actuator Travel In Angular Deg:
2	85.0
A	Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
1	20.0 single section
Ρ	Power Dissipation Rating Per Section In Watts:
1	.0 free air single section
R	Resistance Tolerance Per Section In Percent:
-'	10.0/+10.0 single section
	Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
	0.0 single section
	Shelf Life:
Ν	I/a
	Init Of Measure:

---

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0