## NSN 5905-01-049-2094

Composition Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-049-2094

Electrical Resistance:  1.500 kilohms  Resistance Tolerance In Percent: -10.000/+10.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000  Body Diameter: 0.318 inches
-10.000/+10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter:
Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter:
Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:
Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:
Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:
Reliability Failure Rate Level In Percent:  1.000  Body Diameter:
1.000  Body Diameter:
Body Diameter:
0.318 inches
Body Length:
0.688 inches
Power Dissipation Rating In Watts:
2.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39008/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0