NSN 5905-01-049-2153

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-049-2153 **Section Quantity:** 2 **Body Style:** Rectangular w/tab/flange mounted **Reliability Indicator:** Not established **Thread Length:** 0.900 inches **Mounting Hole Diameter:** 0.200 inches **Shaft Diameter:** 0.190 inches **Shaft Length:** 1.540 inches **Body Length:** 6.110 inches **Body Width:** 0.500 inches **Body Height:** 1.930 inches **Shaft Style:** Round, threaded **Actuator Type:** Single shaft **Longitudinal Actuator Travel:** 3.99 inches **Longitudinal Actuator Effective Electrical Stroke Length:** 3.930 inches **Fragility Factor:** Moderately rugged **Distance Between Mounting Hole Centers:** 1.440 inches **Lateral Distance Between Mounting Hole Centers:** 5.550 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:**

Electrical Resistance Per Section:

Unthreaded hole

5.0 kilohms all sections

NSN 5905-01-049-2153

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Tolerance Per Section:
-1.00/+1.00 all sections
Power Dissipation Rating Per Section In Watts:
0.1 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Tap Location From Ccw Terminal Per Section In Ohms:
1250.0 all sections
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 all sections
Terminal Type And Quantity:
8 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0