NSN 5905-01-049-3135

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-049-3135 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6250 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.625 inches **Undercut Width:** 0.0680 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.750 inches **Body Length:** 1.573 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0

Maximum Starting Torque:

0.40 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

Maximum Stop Torque:

100.00 inch-ounces

Shaft End Play:

0.005 inches

NSN 5905-01-049-3135

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft Runout: |
|--|
| 0.002 inches |
| Lateral Runout: |
| 0.002 inches |
| Pilot Diameter Runout: |
| 0.002 inches |
| Shaft Radial Play: |
| 0.002 inches |
| Fragility Factor: |
| Moderately rugged |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Clamp ring |
| Electrical Resistance Per Section: |
| 2.0 percent, rated amperes c and better flooring |
| Rotary Actuator Travel In Angular Deg: |
| 3600.0 |
| Function Conformity Tolerance Per Section: |
| -0.25/+0.25 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 3.0 7th secondary quality |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -3.0/+3.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Function Characteristic Per Section: |
| 7 oclock all primaries |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Precious Material And Location: |
| Terminal surfaces gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/- |

N/a

NSN 5905-01-049-3135

Precision Wire Wound Variable Resistor - Page 3 of 3



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A002a0