NSN 5905-01-049-3659

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-049-3659

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.200 inches |
| Shaft Diameter: |
| 0.040 inches |
| Shaft Length: |
| 0.035 inches |
| Body Length: |
| 0.250 inches |
| Body Width: |
| 0.175 inches |
| Body Height: |
| 0.250 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| End Application: |
| An/apr-38 |
| Terminal Location: |
| Lower adjacent side two rows |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 1.000 kilohms single section |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.25 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |

85.0 single section

NSN 5905-01-049-3659

Precision Nonwire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0