Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-049-5974

## Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

#### liilength:

0.810 inches

#### Terminal Length:

0.145 inches

#### liiheight:

0.495 inches

#### liiwidth:

0.190 inches

#### Shaft Diameter:

0.100 inches

## Shaft Length:

0.060 inches

# Body Length:

0.750 inches

# Body Width:

0.190 inches

#### Body Height:

0.240 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

5400.0

#### Maximum Starting Torque:

2.10 inch-ounces

#### Maximum Running Torque:

0.70 inch-ounces

#### Center To Center Distance Between Terminals:

0.500 inches

#### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Terminal

#### Center To Center Distance Between Terminal Rows:

0.100 inches

# NSN 5905-01-049-5974

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
5400.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0