## NSN 5905-01-049-9829

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-049-9829 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.109 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.600 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball Switch Type: Rotary **Switch Voltage Rating In Volts:** 120.0 and 28.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 88.0 and 92.0 **Maximum Running Torque:** 30.00 inch-ounces **Maximum Stop Torque:** 100.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.360 inches and 0.390 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** 

Radially positioned over more than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-01-049-9829

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Humidity proof and switch
Electrical Resistance Per Section:
5.0 kilohms all sections
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
35.0 all sections and 45.0 all sections and 55.0 all sections
Rotary Actuator Travel In Angular Deg:
90.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
135.0 all sections
Power Dissipation Rating Per Section In Watts:
1.5 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
3 all sections
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops and spring
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 all sections
Switch Current Type And Rating In Amps:
0.100 ac and 0.100 dc
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A002a0