NSN 5905-01-050-3006

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-050-3006 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** Between 0.124 inches and 0.126 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.169 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round, slotted, undercut Switch Type: Push **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Maximum Stop Torque:** 8.00 inch-ounces **Switch Operating Position:** Any position of rotation travel **Switch Contact Arrangement:** Double pole, single throw, one open, one closed **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): **Terminal Location:**

32.0 Rear-bottom **Mounting Method:** Shaft

NSN 5905-01-050-3006 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Switch
Electrical Resistance Per Section:
2.500 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Switch Current Type And Rating In Amps:
2.000 ac/dc
Standard Taper Curve Per Section:
J single section
Ferminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0