Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-050-3006

Section Quantity:	
1	
Body Style:	
Rectangular bushing mounted	
Reliability Indicator:	
Not established	
Shaft Diameter:	
Between 0.124 inches and 0.126 inches	
Shaft Length:	
0.750 inches	
Mounting Bushing Length:	
0.250 inches	
Body Length:	
1.169 inches	
Body Width:	
0.625 inches	
Body Height:	
0.625 inches	
Shaft Style:	
Round, slotted, undercut	
Switch Type:	
Push	
Switch Voltage Rating In Volts:	
125.0	
Actuator Type:	
Single shaft	
Maximum Stop Torque:	
8.00 inch-ounces	
Switch Operating Position:	
Any position of rotation travel	
Switch Contact Arrangement:	
Double pole, single throw, one open, one closed	
Screw Thread Diameter:	
0.250 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Rear-bottom	
Mounting Method:	
Shaft	

NSN 5905-01-050-3006

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided: Switch **Electrical Resistance Per Section:** 2.500 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Switch Current Type And Rating In Amps: 2.000 ac/dc Standard Taper Curve Per Section: U single section **Terminal Type And Quantity:** 7 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0