

View Online at <https://aerobasegroup.com/nsn/5905-01-050-8176>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.937 inches

Body Diameter:

0.812 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.812 inches

Overall Diameter:

1.062 inches

Shaft Style:

Round

Switch Type:

Rotary

Switch Voltage Rating In Volts:

120.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

0.80 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

0.469 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

75.0 percent, rated amperes c and better finish

Rotary Actuator Travel In Angular Deg:

300.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+8.0 -55 degrees celsius 2nd section and +0.0/+4.0 -25 degrees celsius 2nd section and +0.0/+2.0 0 degrees celsius 2nd section and -3.0/+3.0 85 degrees celsius 2nd section and +0.0/+6.0 120 degrees celsius 2nd section

Function Conformity Tolerance Per Section:

-0.25/+0.25 1st section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

2 1st section

Tap Location Tolerance Per Section:

-1.0/+1.0 ohms all sections

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 2nd section

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

30000.0 1st section and 50500.0 1st section

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Switch Current Type And Rating In Amps:

2.500 ac

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0