NSN 5905-01-050-8991

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-050-8991 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.312 inches **Body Diameter:** 0.812 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.312 inches **Overall Diameter:** 1.062 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 0.80 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.469 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

32.0

Screw Thready Qty Per Inch (tpi):

NSN 5905-01-050-8991

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
200.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+8.0 -55 degrees celsius all sections and +0.0/+4.0 -25 degrees celsius all sections and +0.0/+2.0 0 degrees celsius all sections and
-3.0/+3.0 85 degrees celsius all sections and +0.0/+6.0 120 degrees celsius all sections
Function Conformity Tolerance Per Section:
-0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms all sections
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 all sections
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
100000.0 all sections
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A002a0