

View Online at <https://aerobasegroup.com/nsn/5905-01-051-1063>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.468 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.062 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

0.75 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.531 inches

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.002 inches

Mechanical Backlash In Deg Angular Rotation:

1.0

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

40.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Test Data Document:

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 turret

Specification Data:

81349-mil-r-12934/16 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A002a0