NSN 5905-01-051-4188

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-051-4188

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.094 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
1.266 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 309.0 and 320.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
5.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius all sections and -5.0/+10.0 -25 degrees celsius all sections and -5.0/+10.0 25 degrees celsius all sections and +0.0/+3.0 120 degrees celsius all sections

NSN 5905-01-051-4188

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Resistance Tolerance Per Section In Percent:
10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Test Data Document:
31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
5 tab, solder lug
Specification Data:
31349-mil-r-94/6 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization: