

View Online at <https://aerobasegroup.com/nsn/5905-01-051-5484>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Overall Length:

0.325 inches

Terminal Length:

0.125 inches

Overall Height:

0.400 inches

Overall Width:

0.390 inches

Body Length:

0.200 inches

Body Width:

0.390 inches

Body Height:

0.400 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

280.0

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately delicate

End Application:

Spruance class d (963), los angeles class ssn(688), powhatan class t-atf 166, kidd class ddg, arleigh burke class ddg, virginia classcgn(41), ticonderoga class cg(47), sturgeon class ssn(637) , forrestal class cv, nimitz class cvn

Terminal Location:

Rear end

Mounting Method:

Terminal

Electrical Resistance Per Section:

200.0 ohms c and better flooring

Rotary Actuator Travel In Angular Deg:

280.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Criticality Code Justification:

Feat

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Weapons system essential

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0