

View Online at <https://aerobasegroup.com/nsn/5905-01-051-6029>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.280 inches

Flat Height:

0.080 inches

Body Diameter:

1.160 inches

Mounting Slot Width:

0.060 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.430 inches

Mounting Bushing Length:

0.280 inches

Body Length:

2.000 inches

Shaft Style:

Round, flatted

Actuator Type:

Dual concentric

Nonturn Device Location:

At 9 oclock

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Slot

Electrical Resistance Per Section:

2.500 percent, rated amperes c and better industrial clears

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary finish

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A002a0