

View Online at <https://aerobasegroup.com/nsn/5905-01-051-6029>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**First Flat Length:**

0.280 inches

**Flat Height:**

0.080 inches

**Body Diameter:**

1.160 inches

**Mounting Slot Width:**

0.060 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.430 inches

**Mounting Bushing Length:**

0.280 inches

**Body Length:**

2.000 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Dual concentric

**Nonturn Device Location:**

At 9 oclock

**Mounting Facility Quantity:**

3

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Slot

**Electrical Resistance Per Section:**

2.500 percent, rated amperes c and better industrial clears

**Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:**

340.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-30.0/+30.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 7th secondary finish

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A002a0