

View Online at <https://aerobasegroup.com/nsn/5905-01-053-1408>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.344 inches

Flat Height:

0.219 inches

Body Diameter:

1.250 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.906 inches

Shaft Style:

Round, flatted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Double pole, double throw

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

320.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Switch Current Type And Rating In Amps:

3.000 ac

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0