## NSN 5905-01-053-2743

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-053-2743

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Terminal Length:
0.625 inches
Body Diameter:
0.270 inches
Shaft Diameter:
0.025 inches
Shaft Length:
0.095 inches
Body Length:
0.215 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
240.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
0.200 inches  Terminal Location:
Terminal Location:
Terminal Location: Rear end
Terminal Location: Rear end Mounting Method:
Terminal Location: Rear end Mounting Method: Terminal
Terminal Location: Rear end Mounting Method: Terminal Center To Center Distance Between Terminal Rows:
Terminal Location: Rear end Mounting Method: Terminal Center To Center Distance Between Terminal Rows: 0.100 inches
Terminal Location: Rear end Mounting Method: Terminal Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section:
Terminal Location: Rear end Mounting Method: Terminal Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section: 250.000 ohms single section
Terminal Location: Rear end Mounting Method: Terminal Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section: 250.000 ohms single section Rotary Actuator Travel In Angular Deg:
Terminal Location: Rear end Mounting Method: Terminal Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section: 250.000 ohms single section Rotary Actuator Travel In Angular Deg: 240.0

150.0 single section

## NSN 5905-01-053-2743

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature C	Coefficient Of	Resistance	Per Section	on In Ppm	Per Deg (	Celsius:
-100.0/+100.0 s	single section					

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0