NSN 5905-01-053-3908

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-053-3908

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0 Electrical Resistance: 0.0625 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s) Shelf Life:	
Electrical Resistance: 0.0625 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	-20.0/+20.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.824 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	0.0625 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	275.0
Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	-55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Encased
Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Terminal Type:
Not established Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Wire lead
Terminal Length: 2.000 inches Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Reliability Indicator:
Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Not established
Body Length: 1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Terminal Length:
1.937 inches Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	2.000 inches
Body Width: 0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Body Length:
0.844 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	1.937 inches
Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Body Width:
0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	0.844 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Body Height:
1.562 inches Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	0.625 inches
Power Dissipation Rating In Watts: 50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
50.000 free air Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	1.562 inches
Mounting Hole Size: 0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	Power Dissipation Rating In Watts:
0.125 inches Special Features: 4 terminals Style Designator: Axial terminal (s)	50.000 free air
Special Features: 4 terminals Style Designator: Axial terminal (s)	Mounting Hole Size:
4 terminals Style Designator: Axial terminal (s)	0.125 inches
Style Designator: Axial terminal (s)	Special Features:
Axial terminal (s)	4 terminals
	Style Designator:
Shelf Life:	Axial terminal (s)
	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:
Demilitarization:	Demilitarization:

No

NSN 5905-01-053-3908

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0