NSN 5905-01-054-3359

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-054-3359

Electrical Resistance: 10.000 ohms Resistance Tolerance In Percent: 10.000 /-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Range Of Tempurature Range Of Tempurature Range Of
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: 55.0/+275.0 Inclosure Method: 56.0/+275.0 Inclosure Method: 57.0 Sincapsulated Ferminal Type: Wire lead Reliability Indicator: 25tablished Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 1.0312 inches 880dy Length: 1.0475 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 3.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 nclosure Method: ====================================
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.312 inches Body Length: 0.0875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Fest Data Document:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: 0,312 inches Body Length: 0,875 inches Power Dissipation Rating In Watts: 7,000 free air Style Designator: Axial terminal each end Fest Data Document:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: 0,312 inches Body Length: 0,875 inches Power Dissipation Rating In Watts: 7,000 free air Style Designator: Axial terminal each end Fest Data Document:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: 0,312 inches Body Length: 0,875 inches Power Dissipation Rating In Watts: 7,000 free air Style Designator: Axial terminal each end Fest Data Document:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: 0,312 inches Body Length: 0,875 inches Power Dissipation Rating In Watts: 7,000 free air Style Designator: Axial terminal each end Fest Data Document:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Fest Data Document:
Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
1.000 Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
D.312 inches Body Length: D.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Fest Data Document:
Body Length: 0.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
D.875 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document:
7.000 free air Style Designator: Axial terminal each end Test Data Document:
Style Designator: Axial terminal each end Test Data Document:
Axial terminal each end Test Data Document:
Test Data Document:
21240 mil r 20007/40 appointation (includes angineering type hulleting, breakures, etc., that reflect appointation type data in appointant
31349-mil-r-39007/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg: