

View Online at <https://aerobasegroup.com/nsn/5905-01-054-3392>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Terminal Length:**

0.234 inches

**First Flat Length:**

Between 0.234 inches and 0.266 inches

**Flat Height:**

Between 0.092 inches and 0.096 inches

**Body Diameter:**

Between 0.484 inches and 0.516 inches

**Shaft Diameter:**

Between 0.122 inches and 0.126 inches

**Shaft Length:**

0.750 inches

**Mounting Bushing Length:**

Between 0.237 inches and 0.266 inches

**Body Length:**

Between 0.437 inches and 0.469 inches

**Shaft Style:**

Round, flatted

**Contact Arm Electrical Off Position:**

Fully ccw

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 6 oclock

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

250.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 350.0 and 360.0

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Test Data Document:**

98230-0n503111-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0