Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-054-4184

Section	Quantity:	

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.140 inches

**Body Length:** 

0.234 inches

**Body Width:** 

0.4375 inches

**Body Height:** 

0.359 inches

Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

270.0

**Center To Center Distance Between Terminals:** 

0.200 inches

**Fragility Factor:** 

Moderately delicate

## **Terminal Location:**

Lower adjacent side single row

#### Mounting Method:

Terminal

#### **Features Provided:**

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

5.0 megohms single section

**Rotary Actuator Travel In Angular Deg:** 

270.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## **Actuator Travel Control Feature:**

Stops

## Standard Taper Curve Per Section:

A single section

## **Terminal Type And Quantity:**

3 pin

# NSN 5905-01-054-4184

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0