## NSN 5905-01-054-5408

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-054-5408 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.468 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.125 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.062 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 0.75 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.531 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.001 inches **Shaft Radial Play:** 

0.002 inches

Mechanical Backlash In Deg Angular Rotation:

0.1

## NSN 5905-01-054-5408

Precision Wire Wound Variable Resistor - Page 2 of 3



Frag	ilitv	Factor:

Moderately rugged

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

1.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

360.0

**Function Conformity Tolerance Per Section:** 

-0.25/+0.25 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

**Function Characteristic Per Section:** 

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Test Data Document:** 

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

3 turret

**Specification Data:** 

81349-mil-r-12934/16 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5905-01-054-5408

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0