

View Online at <https://aerobasegroup.com/nsn/5905-01-054-6227>

**Section Quantity:**

3

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.9683 inches and 0.9688 inches

**Pilot Length:**

Between 0.0570 inches and 0.0670 inches

**Overall Length:**

2.291 inches

**Undercut Diameter:**

0.975 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

1.092 centimeters

**Shaft Diameter:**

Between 0.1245 inches and 0.1248 inches

**Shaft Length:**

Between 0.4687 inches and 0.5313 inches

**Body Length:**

1.760 inches

**Overall Diameter:**

1.092 inches

**Mounting Lip Diameter:**

Between 1.0520 inches and 1.0670 inches

**Mounting Lip Depth:**

0.0570 mils and 0.0670 centimeters

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

345.0

**Maximum Starting Torque:**

0.20 inch-ounces

**Maximum Running Torque:**

0.20 inch-ounces

**Shaft End Play:**

0.00500 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.00100 inches

**Shaft Radial Play:**

0.001 inches

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Cubic Measure:**

2.146 cubic inches

**Electrical Resistance Per Section:**

100.0 percent, rated amperes c and better

**Rotary Actuator Travel In Angular Deg:**

360.0

**Resistance Temperature Characteristic Range Per Section In Percent:**

-5.0/+5.0 -65 degrees celsius all sections and -4.0/+4.0 -15 degrees celsius all sections and -2.5/+2.5 50 degrees celsius all sections and -5.0/+5.0 75 degrees celsius all sections and -5.0/+5.0 105 degrees celsius all sections and -5.0/+5.0 125 degrees celsius all sections

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.25 7th secondary at 10'30 oclock

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

6 oclock all primaries

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Terminal Type And Quantity:**

9 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0