

View Online at <https://aerobasegroup.com/nsn/5905-01-055-3730>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Terminal Length:

Between 0.156 inches and 0.186 inches

First Flat Length:

Between 0.234 inches and 0.266 inches

Flat Height:

Between 0.092 inches and 0.096 inches

Body Diameter:

Between 0.484 inches and 0.516 inches

Shaft Diameter:

Between 0.234 inches and 0.266 inches

Shaft Length:

0.562 inches

Mounting Bushing Length:

Between 0.594 inches and 0.843 inches

Body Length:

0.625 inches

Shaft Style:

Round, flatted

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Nonturn Device Location:

At 12 oclock and at 3 oclock

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

250.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

32.5

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Test Data Document:

98230-0n241689-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0