NSN 5905-01-055-5581

Film Fixed Resistor Network - Page 1 of 2



| view Online at https://aerobasegroup.com/hsn/5905-01-055-5561 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -300.0/+300.0 |
| Electrical Resistance: |
| 10.000 kilohms |
| Resistance Tolerance In Percent: |
| -2.000/+2.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 14 |
| Terminal Type: |
| Pin |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.135 inches |
| Body Length: |
| 0.740 inches |
| Body Width: |
| 0.270 inches |
| Body Height: |
| 0.200 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 0.100 each resistor |
| Identical Value Resistor Quantity: |
| 7 each resistor |
| Maximum Tolerance Deviation In Percent: |
| -0.01/+0.01 |
| Style Designator: |
| Dual inline |
| Test Data Document: |
| 81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/1 government specification

NSN 5905-01-055-5581

Film Fixed Resistor Network - Page 2 of 2



| _ | | | | |
|---|-----|------|---|------|
| c | hο | JIF. | | ife: |
| J | 116 | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0