Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-057-0744

# Section Quantity: 1 Body Style: Rectangular w/mounting holes

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

## 0.010

Overall Length:

0.545 inches

Terminal Length:

0.172 inches

## **Overall Height:**

0.687 inches

**Overall Width:** 

## 0.180 inches

Mounting Hole Diameter:

0.073 inches

#### Shaft Diameter:

0.078 inches

## Shaft Length:

0.045 inches

## **Body Length:**

0.500 inches

## **Body Width:**

0.180 inches

## **Body Height:**

0.515 inches

## Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

Between 7200.0 and 15120.0

## Center To Center Distance Between Terminals:

0.200 inches

## Fragility Factor:

Moderately delicate

# Lateral Distance Between Mounting Hole Centers:

0.520 inches

## **Mounting Facility Quantity:**



| Terminal Location:   |
|--|
| Lower adjacent side single row   |
|  |
| Terminal and unthreaded hole   |
| Electrical Resistance Per Section:   |
| 200.0 ohms c and better flooring   |
| Rotary Actuator Travel In Angular Deg:   |
| Between 7200.0 and 15120.0   |
| Center To Center Distance Between Center Terminal And Outside Terminal:  |
| 0.100 inches   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  |
| 150.0 single section   |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:  |
| -50.0/+50.0 single section   |
| Power Dissipation Rating Per Section In Watts:   |
| 0.75 7th secondary quality   |
| Resistance Tolerance Per Section In Percent:   |
| -5.0/+5.0 single section   |
| Actuator Travel Control Feature:   |
| Clutch   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  |
| 85.0 single section  |
| Standard Taper Curve Per Section:  |
| A single section   |
| Test Data Document:  |
| 81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 3 pin  |
| Specification Data:  |
| 81349-mil-r-39015/2 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A002a0   |
|  |