Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-057-8394

## Section Quantity:

1

Body Style:

Cylindrical servo mounted

## **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

0.7500 inches

#### **Pilot Length:**

0.0620 inches

#### **Undercut Diameter:**

2.875 inches

#### **Undercut Width:**

0.0930 inches

#### **Body Diameter:**

## 3.000 inches

Angle Of Mounting Hole In Deg:

90.0

#### Angle Between Centerlines Of Mounting Holes In Deg:

120.0

#### Shaft Diameter:

0.250 inches

## Shaft Length:

0.438 inches

#### **Body Length:**

1.850 inches

## Mounting Lip Diameter:

3.0000 inches

#### Mounting Lip Depth:

0.0620 inches

## Mounting Hole/stud Circle Diameter:

1.750 inches

#### Shaft Style:

Round

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

360.0

## Maximum Starting Torque:

0.50 inch-ounces

## Maximum Running Torque:

0.50 inch-ounces

# NSN 5905-01-057-8394

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
5.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation
120.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-0.5/+0.5 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a

Unit Of Measure:

---

## NSN 5905-01-057-8394

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0