Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-058-6698

# Section Quantity:

1

Body Style:

Rectangular

# **Reliability Indicator:**

Not established

#### **Overall Length:**

0.300 inches

#### Terminal Length:

0.187 inches

#### **Overall Height:**

0.587 inches

#### **Overall Width:**

0.365 inches

#### Body Length:

## 0.180 inches

#### **Body Width:**

0.365 inches

# **Body Height:**

0.415 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

230.0

#### Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

1.0 percent, rated amperes c and better flooring

#### Rotary Actuator Travel In Angular Deg:

360.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality



**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

## Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0