Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-058-9855

# Section Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

### **Terminal Length:**

0.312 inches

**Body Length:** 

0.290 inches

**Body Width:** 

#### 0.245 inches

Body Height:

#### 0.360 inches

Actuator Type:

#### Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### Maximum Starting Torque:

5.00 inch-ounces

## Maximum Running Torque:

5.00 inch-ounces

## Center To Center Distance Between Terminals:

0.200 inches

### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Terminal

#### Center To Center Distance Between Terminal Rows:

0.100 inches

#### **Electrical Resistance Per Section:**

100.0 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

240.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

### Power Dissipation Rating Per Section In Watts:

0.5 free air single section



**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

### Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0