NSN 5905-01-059-9233

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-059-9233

Section Quantity:
Section Quantity:
Body Style:
Rectangular w/mounting holes
Terminal Length: 0.500 inches
Mounting Hole Diameter: 0.078 inches
Body Length:
0.500 inches
Body Width:
0.220 inches
Body Height:
0.500 inches
Actuator Type:
Integral knob
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.470 inches and 0.620 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Features Provided:
Humidity proof
Electrical Resistance Per Section:
200.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-01-059-9233

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Special Features:
25 turn adjustment
Terminal Type And Quantity:
2 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0