

View Online at https://aerobasegroup.com/nsn/5905-01-060-0387

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.875 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.812 inches

Mounting Bushing Length:

0.312 inches

Body Length:

1.457 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3610.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Shaft End Play:

0.00850 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.003 inches

Screw Thread Diameter:

0.375 inches



Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Features Provided:** Shaft locking device **Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.05/+0.05 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 turret Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0