NSN 5905-01-060-2188

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-060-2188 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.188 inches **Terminal Length:** 0.500 inches **Body Diameter:** 0.312 inches **Body Length:** 0.188 inches **Overall Diameter:** 0.310 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 6.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Cubic Measure:** 0.014 cubic inches **Electrical Resistance Per Section:** 200.0 ohms c and better flooring

Rotary Actuator Travel In Angular Deg: 300.0

NSN 5905-01-060-2188

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -70.0/+70.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 7th secondary quality **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:** Demilitarization: No