NSN 5905-01-060-2189

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-060-2189

View Online at https://aerobasegroup.com/nsn/5905-
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Pilot Diameter:
Between 1.02900 inches and 1.03000 inches
Pilot Length:
Between 0.03000 inches and 0.50000 inches
Undercut Diameter:
Between 1.029 inches and 1.030 inches
Undercut Width:
Between 0.05000 inches and 0.70000 inches
Body Diameter:
Between 1.080 inches and 1.110 inches
Shaft Diameter:
Between 0.124 inches and 0.125 inches
Shaft Length:
Between 0.310 inches and 0.330 inches
Body Length:
0.635 inches
Mounting Lip Diameter:
Between 1.08000 inches and 1.11000 inches
Mounting Lip Depth:
Between 0.05000 inches and 0.70000 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Maximum Starting Torque:
0.20 inch-ounces
Mounting Method:
Flange
Electrical Resistance Per Section:
10.000 kilohms single section
Function Conformity Per Section:
Single section absolute conformity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5905-01-060-2189

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	atio	

No

Fiig:

A002a0