Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-060-2189

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Pilot Diameter:

Between 1.02900 inches and 1.03000 inches

Pilot Length:

Between 0.03000 inches and 0.50000 inches

Undercut Diameter:

Between 1.029 inches and 1.030 inches

Undercut Width:

Between 0.05000 inches and 0.70000 inches

Body Diameter:

Between 1.080 inches and 1.110 inches

Shaft Diameter:

Between 0.124 inches and 0.125 inches

Shaft Length:

Between 0.310 inches and 0.330 inches

Body Length:

0.635 inches

Mounting Lip Diameter:

Between 1.08000 inches and 1.11000 inches

Mounting Lip Depth:

Between 0.05000 inches and 0.70000 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Maximum Starting Torque:

0.20 inch-ounces

Mounting Method:

Flange

Electrical Resistance Per Section:

10.000 kilohms single section

Function Conformity Per Section:

Single section absolute conformity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A002a0