Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-060-4474

# Section Quantity:

1

Body Style:

Rectangular

# **Reliability Indicator:**

Not established

## **Terminal Length:**

0.500 inches

#### Shaft Diameter:

0.070 inches

#### Shaft Length:

0.040 inches

### **Body Length:**

0.312 inches

### Body Width:

0.175 inches

# Body Height:

0.312 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

360.0

## Maximum Starting Torque:

3.00 inch-ounces

## Maximum Running Torque:

3.00 inch-ounces

## Center To Center Distance Between Terminals:

0.200 inches

## **Terminal Location:**

Left adjacent side single row

### **Mounting Method:**

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

## **Electrical Resistance Per Section:**

10.000 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

5400.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0/+70.0 single section **Power Dissipation Rating Per Section In Watts:** 0.6 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops and clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0