NSN 5905-01-060-5335

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-060-5335

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Rectangular w/mounting holes/slots |
| Mounting Hole Diameter: |
| 0.087 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.062 inches |
| Body Length: |
| 1.250 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.328 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 9000.0 |
| Lateral Distance Between Mounting Hole Centers: |
| 1.000 inches |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Unthreaded hole |
| Electrical Resistance Per Section: |
| 100.000 ohms single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 200.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 5.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 25.0 single section |
| Terminal Type And Quantity: |
| 3 wire lead |

3 wire lead

NSN 5905-01-060-5335

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Shelf Life: |
|------------------|
| N/a |
| Unit Of Measure: |
| |
| Domilitarization |

Demilitarization:

No

Fiig:

A002a0