NSN 5905-01-061-1214

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-061-1214

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Cylindrical |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.187 inches |
| Body Diameter: |
| 0.500 inches |
| Body Length: |
| 0.325 inches |
| Actuator Type: |
| Integral knob |
| Maximum Starting Torque: |
| 7.50 inch-ounces |
| Maximum Running Torque: |
| 7.50 inch-ounces |
| Maximum Stop Torque: |
| 30.00 inch-ounces |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 500.000 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 320.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -70.0/+70.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |

Stops

NSN 5905-01-061-1214

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
|---|
| 50.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |